

Tegund	Þykkt	USB	LAN	WiFi	CF rauf	RS-232	Parallel	2,5" HDD
eBox-4300-H	35	3	1		X			V
eBox-4300-JSK	35	3	1	V	X	2		
eBox-4300-JSK og þráðlausu neti	35	3	1	X	X	2		

Skýringar: X=fylgir, V=Valkostur

CPU	VIA Eden ULV 500MHz
System Memory	Onboard 512MB DDRAM
System chipset	VIA CX700M
I/O Chip	Winbond W83697
Flash	Support EmbedDisk 32MB to 2GB 44 Pin Horizontal type
Display memory	8/16/32/64/128 MB share system memory
Graphic	Connect to any VESA standard monitor up to 1920 x 1440 resolution
Audio	2.2 (Codec) VIA Vinyl VT1708
Audio Interface	Mic In, Line out
Serial Port	2 x RS-232 (eBox-4300-JSK)
USB	3 x USB 2.0 Ports (Two at front)
Keyboard / Mouse	PS/2 for keyboard & Mouse
Network	Realtek RTL8100B 10/100 Mbps Fast Ethernet
Remote Boot ROM	built-in boot ROM function
Power Requirement	Single Voltage +5V @3A
Operating Temperature	0 ~ 60 C
Size (W x H x D)	115 x 115 x 35 mm
Weight	505g
Certification	CE, FCC



Tegund	Þykkt	USB	LAN	WiFi	CF rauf	RS-232	Parallel	2,5" HDD
eBox-3800SL	38	2	1					
eBox-3851	56	2	1	V	X		X	V
eBox-3852	56	2	2	V	X	1	X	
eBox-3854	56	6	1	V	X			

Skýringar: X=fylgir, V=Valkostur

Processor	Onboard VIA EDEN Nano BGN processor
System Memory	Onboard 256MB DDRAM
System chipset	VIA CLE266/ VT8235
I/O Chip	VIA VT1211
Flash	Support EmbedDisk 32MB to 2GB 44 Pin Horizontal type
Display memory	8/16/32/64 MB share system memory
Graphic	Connect to any VESA standard monitor up to 24 bit color/ 1280 x 1024 resolution
Audio	Full 16 bit stereo
Parallel Port	1 x Printer (eBox-3851, 3852)
Serial Port	1 x RS-232 (eBox-3852)
USB	USB 2.0 Ports (one at front)
Keyboard / Mouse	PS/2 for keyboard & Mouse
Network	10/100 Mbps Fast Ethernet
Management	PXE BIOS for image network boot
Power Requirement	Single Voltage +5V @4A
Operating Temperature	-20 ~ 60 C
Size (W x H x D)	170 x 124 x 38 mm or 170 x 124 x 58 mm
Weight	940g / 2lbs
Certification	CE, FCC